


WIRE ROPE


STAINLESS STEEL CABLE

(TYPE 304 6X19, 6X36, 1X19)


According to Federal Specification RR-W-410D, preformed, right regular lay.



6 X 19 IWRC



6 x 36 IWRC
WARRINGTON SEALE



1 X 19

Diameter In Inches	6 X 19 STAINLESS STEEL TYPE 304		6 X 36 TYPE 304
	Approx. weight per Foot in pounds	Breaking strength in Pounds*	Breaking strength in Pounds*
5/16"	0.18	-	8,300
3/8"	0.24	12,000	11,700
7/16"	0.35	16,300	15,800
1/2"	0.46	22,800	20,800
9/16"	0.59	28,500	25,600
5/8"	0.72	35,000	31,400
3/4"	1.04	49,600	44,400
7/8"	1.42	66,500	59,700
1"	1.85	85,400	77,300

Diameter In Inches	1 X 19 STAINLESS STEEL STRAND TYPE 316	
	Approx. weight per 1000 Ft. in pounds	Breaking strength in Pounds*
1/8"	35	2,100
3/16"	77	4,700
1/4"	135	8,200
5/16"	210	12,500
3/8"	300	17,500

*Listed for comparison only. Actual operating loads may vary, but should never exceed the recommended design factor or 20% of catalog Breaking Strength.